

Trailer Tires



High Speed Trailer Tires

Part #	Size	Ply Rating	S.W. (Inches)	O.D. (Inches)	Max Load Capacity at 60 mph	Max PSI	Rim Size
	4.80/4.00-8	2PR TL	4.6"	16.0"	390 lb.	30 PSI	8"x 3.75"
	4.80/4.00-8	4PR TT, TL	4.6"	16.1"	590 lb.	60 PSI	8"x 3.75"
	4.80/4.00-8	6PR TT, TL	4.7"	16.1"	745 lb.	75 PSI	8"x 3.75"



High Speed Trailer Tires

Part #	Size	Ply Rating	S.W. (Inches)	O.D. (Inches)	Max Load Capacity at 60 mph	Max PSI	Rim Size
	5.70-8	4PR TL	5.8"	18.1"	715 lb.	50 PSI	8"x 3.75"
	5.70-8	6PR TL	5.9"	18.0"	910 lb.	75 PSI	8"x 3.75"
	5.70-8	8PR TL	5.9"	18.0"	1075 lb.	100 PSI	8"x 3.75"
	4.80-12	4PR TL	4.8"	20.5"	780 lb.	60 PSI	12" x 4"
	4.80-12	6PR TL	4.8"	20.5"	990 lb.	90 PSI	12"x 4"
	5.30-12	4PR TL	5.6"	21.9"	840 lb.	55 PSI	12"x 4"
	5.30-12	6PR TL	5.6"	21.9"	1045 lb.	80 PSI	12"x 4"
	5.30-12	8PR TL	5.6"	21.9"	1250 lb.	105 PSI	12"x 4"

Please Note: Specifications May Vary by Manufacturer